

Technical Specifications

BASIC PA SYSTEM

AP-200P/M

COST EFFECTIVE MIXER AMP

Design	
(i) INDICOMA	

Key I	Features			
	3 Microphone and 2 auxiliary input,	1 lii	ne input	
	100V,70V and 4-16Ohms tran	sfo	rmer-isol	ated
	speaker outputs			
	Automatic mute function for	·\ \	paging	and
	announcements			
	Individual input gain controls with r	nas	ter volum	ie
	Bass & Treble tone controls, LED le	vel	meter	
	Speaker output short circuit protect	tion		
	Fan works when temperature highe	r tha	an 35 °C	
	AP-200M comes with USB,MP3 and	turi	ner AM/FI	И

Technical Specifications	
Rated Power Output	70W
Output Regulation	Less than 3 dB (no load to full load)
Speaker Output	70 ohms (70V), Low impedance: 4-16 ohms, 143 ohms (100V)
Frequency Response	60-18,000HZ (+/-3dB)
THD	Less than 0.5% at 1kHz (1/3 Rated Power); <= 2% (Rated Power)
S/N ratio	Line: 76dB, Mic: 68dB
Input	MIC 1, 2, 3: 600 ohms, 5mV, unbalanced, phone jack; AUX 1, 2: 10k ohms, 300mV, unbalanced, RCA jack
Output	600 ohms, >1.3V, RCA jack
Power Requirements	AC 220 V+-10% / 50Hz, 24VDC
Power Consumption	85 W
Dimensions	89(H) x 483(W) x 366(D) mm

TKOKO – a brand owned by Honeywell Audiovisuals, is committed to provide customers around the globe with reliable, user-friendly, and lowest cost competitive audio management solutions that are in accordance with international standards.