AP-98 BASIC PA SYSTEM

AP-600P/M

COST EFFECTIVE MIXER AMP

Must been depight all \$1/10/25 and \$1/10/25	other wich

ey i	reatures			
	3 Microphone and 2 auxiliary input, 1 line input			
	100V,70V and 4-16Ohms transformer-isolated			
	speaker outputs			
	Automatic mute function for paging and			
	announcements			
	Individual input gain controls with master volume			
	Bass & Treble tone controls, LED level meter			
	Speaker output short circuit protection			
	Fan works when temperature higher than 35 °C			
	AP-600M comes with USB,MP3 and turner AM/FM			

Technical Specifications		
Rated Power Output	260W	
Output Regulation	Less than 3 dB (no load to full load)	
Speaker Output	19 ohms (70V), Low impedance: 4-16 ohms, 39 ohms (100V)	
Frequency Response	60-18,000HZ (+/-3dB)	
THD	Less than 0.5% at 1kHz (1/3 Rated Power); <= 2% (Rated Power)	
S/N ratio	Line: 76dB, Mic: 68dB	
Input	MIC 1, 2, 3: 600 ohms, 5mV, unbalanced, phone jack; AUX 1, 2: 10k ohms, 300mV, unbalanced, RCA jack	
Output	600 ohms, >1.3V, RCA jack	
Power Requirements	AC 220 V+-10% / 50Hz, 24VDC	
Power Consumption	350 W	
Dimensions	89(H) x 483(W) x 366(D) mm	

TKOKO – a brand owned by Honeywell Audiovisuals, is committed to provide customers around the globe with reliable, user-friendly, and lowest cost competitive audio management solutions that are in accordance with international standards.