AP-98 BASIC PA SYSTEM

AP-9813B/D

SPEAKER SELECTOR



Key	Features
	10 zone speaker selector & router
	02 amplifier inputs (A and B)
	Control up to 10 speaker zones
	Ability to select zones when receiving an alarm signal to switch from input A (BGM signal) to input B (Alarm sound signal) to the corresponding zones automatically

☐ AP-9813D comes with 25-Pin Fire Alarm Signal Input

Technical Specifications		
Inputs	INPUT A: Background Music Signal (100V, 70V) INPUT B: Warning Sound Signal (100V, 70V)	
Alarm Outputs	Two ports output short-circuit signals	
Zone Outputs	10 channels, total capacity <1500W	
Controls	10 pushbutton zone selectors, 1 power switch	
THD	<0.01 at 1kHz	
Alarm Level	Low electric signal is valid, U in <0.3V	
Protection	AC FUSE (0.5A) X 1	
Power Requirements	AC 220 V+-10% / 50~60Hz <10VA	
Power Consumption	10 ~ 20 W	
Dimensions	89(H) x 483(W) x 366(D) mm	

TKOKO – a brand owned by Honeywell Audiovisuals, is committed to provide customers around the globe with reliable, user-friendly, and lowest cost competitive audio management solutions that are in accordance with international standards.