

## M-5120/240/300

## SELF MOUNT AMPLIFIER 5 ZONE

### Design



### Key Features

- 6 Channel Volume Control, Chime & Siren switch
- 5 Zone Speaker Selector & 7 Band EQ Control
- Priority & Phantom Power Switch for CH 1 & 2
- Trim Pot Control for 6 Input Channel, Level Control for Chime & Siren
- Telephone Paging output
- Connect to remote call station with 5 zone selector

Technical Specifications		M-5120	M-5240	M-5300
Rate Power (RMS)		120 Watt	240 Watt	300 Watt
Input Sensitivity/Impedance	Channels 1-5	-54 dB to -10 dB Variable/ 20 k ohm Unbalanced		
	Channels 6	-34 dB to +10 dB Variable / 47 k ohm Unbalanced		
	Tele-Paging	0 dB / 600 ohm Balanced		
	Amp in, Link in	0 dB / 10 k ohm		
	Speaker Output	100 V (165 ohm), 70 V (83 ohm), 25V (10.4 ohm), 15.5 V (4 ohm)		
	Pre-Amp Out, Link Out	0 dB / 600 ohm		
Frequency Response (-3dB)		50 Hz – 20 kHz		
T.H.D (1 kHz, Rated Power) / Signal to Noise Ratio		< 1% / > 100dB		
Graphic Equalizer		+/- 12 dB 125 Hz, 250 Hz, 500 Hz, 1 kHz, 2 kHz, 4 kHz, 8 kHz		
Power Source		AC 100~240 V , 50/60 Hz		

**TKOKO** – a brand owned by **Honeywell** Audiovisuals, is committed to provide customers around the globe with reliable, user-friendly, and lowest cost competitive audio management solutions that are in accordance with international standards.