

CEILING SPEAKER

DESCRIPTION:

Model: CH-705/6"

Full-range 6-1/2", 6 W dual-cone dynamic speaker. 100 V line transformer features two taps for 3 W and 6 W outputs. Screw type compression terminals provide secure, low-noise connections and easy installation. Attractive cream color ABS resin finish with complementary off-white grille suits any decor.

SPECIFICATIONS:

l	
Туре	Flush-mount in-ceiling
Enclosure	Open frame type
Speaker Unit	6-1/2" dual-cone, paper
Rated Power	6 W, 100 V line transformer
Rated Impedance	100V: 1.7k ohms (6 W), 3.3k ohms (3 W); 70V: 1.7k ohms (3W), 3.3k ohms (1.5W)
Sound Pressure Level	90 dB (1 W, 1 m)
Frequency Response	110 - 13 kHz
Terminals	Compression screw connectors
Finish	Baffle : ABS resin, Cream (RAL 9001 or equivalent color) Enclosure : ABS resin, Cream (RAL 9001 or equivalent color) Grille : Steel alloy net, Off-white (RAL 9010 or equivalent color) Mounting Hardware : Steel alloy, corrosion resistant
Dimensions	Ф230 X 90 (D) mm
Dimensions for mounting	Ф200 mm
Weight	870 grams
Mounting Method	Frame-mounted spring-loaded clamps

APPEARANCE:







